

Standard Roofers Kit - KTRSTD

- LINQ Essential harness H101
- WLO1SNSN Shock Absorbing Webbing Lanyard Single Leg (with 2 x Snap Hooks) x 1
- RKR015 Rope kernmantle with thimble eye & rope grab. 15M with permanently attached shock absorbing 450mm assembly and screw gate karabiner
- HSASE2515 Anchor Strap Endless 25mm - 1.5M x 1
- KSGSA18 Screw Gate Karabiner x 2
- Kernmantle rope exceeds 14.7kN
- 110gm of polyester as opposed to 65gm. This results in exceptional strength capabilities
- Rope grab as per restraint technique, in order to ensure stopping force is less than 6kN, rope grab should always be used in conjunction with a shock absorbing element
- Batch tested to AS/NZS 1891.1: 3.8m drop using 100kg test weight, reducing forces to under 4.5kN
- An exclusive Extended Length Energy Absorber (ELEA) designed to protect a workers, of up to 160kg, tools and equipment
- Drop forged lanyard hardware for added strength in case of extreme conditions
- Contrast stitch thread colour for easy inspection and AS/NZS 1891.1 compliance
- Pebble weave webbing provides maximum grip precluding incidental buckle slippage
- Combined belay loop sub pelvic strap positioning reduces risk of throat and facial injury at moment of impact
- Retro-reflectivity built into webbing
- 160kg wearer capacity (combined weight of wearer, clothing and tools) when used in conjunction with LINQ shock absorbing lanyard
- Articulated chest and shoulder straps adjustment points designed for female wearers
- Contrast stitch thread colour for easy inspection and AS/NZS 1891.1 compliance
- Unique to LINQ - Green for safely locked - Red for not locked feature / indicator
- Available with Kit Bag, Round Bucket or Square Bucket