LIFTING INSPECTION SERVICES



Single Leg Elasticated Lanyard - WLE1

- 1.85M Elasticated Lanyard
- WLE1- Single Leg Elasticated Lanyard + hardware (see list below)
- An exclusive Extended Length Energy Absorber (ELEA) designed to protect a worker of up to 160kg including tools and equipment.
- Drop forged lanyard hardware
- Stitching patterns are sewn by computer-controlled bar tacking machinery for precision using
 UV resistant high tenacity polyester yarn with 100 newton (10kg) breaking strength.
- Unique THETA stitch pattern has 423 stitches resulting in a strength that matches the lanyards webbing strength.
- Unique stretchable lanyard design that minimises length of lanyard, preventing tripping or snagging.
- Australian designed, engineered, and made.
- Webbing Tenacity= 23kN.
- Webbing is UV rated to meet AS/NZS 1891.1 standard
- THETA stitch pattern (equals 3300kg strength). Engineered to match webbing strength to ensure no weak point in the harness assembly.

Available with end fitting combinations: -

KTKT – Triple Action Karabiner Each end (STANDARD)

KTST - Triple Action Karabiner and Triple Action Scaffold Hook (STANDARD)

Optional versions available on request only

SNSN - Snap Hook Each end

SNSD – Snap Hook and Double Action Scaffold Hook

SNKT - Snap Hook and Triple Action Karabiner

KDKD - Double Action Karabiner Each end

KDSD - Double Action Karabiner and Double Action Scaffold Hook

KDSN – Double Action Karabiner and Snap Hook

KDST - Double Action Karabiner and Triple Action Scaffold Hook

KSKS - Karabiner Screw Gate Each end

KSKD - Karabiner Screw Gate and Double Action Karabiner

KSSD - Karabiner Screw Gate and Double Action Scaffold Hook

KSSN - Karabiner Screw Gate and Snap Hook

KSST - Karabiner Screw Gate and Triple Action Scaffold Hook

KTSD - Triple Action Karabiner and Double Action Scaffold Hook

KTSN – Triple Action Karabiner and Snap Hook

SNST - Snap Hook and Triple Action Scaffold Hook