

Single Leg Shock Absorbing Webbing Lanyard – WLO1

- 2M Webbing Lanyard
- WLO1- Single Leg Webbing Lanyard + hardware (see list below)
- An exclusive Extended Length Energy Absorber (ELEA) designed to protect a worker of up to 160kg including tools and equipment.
- Drop forged lanyard hardware
- Unique THETA stitch pattern has 423 stitches resulting in a strength that matches the lanyards webbing strength.
- Australian designed, engineered, and made.
- Webbing Tenacity = 33kN.
- THETA stitch pattern (equals 3300kg strength). Engineered to match webbing strength to ensure no weak point in the harness assembly.
- BSI Certified and approved to AS/NZS 1891.1
- THETA stitch pattern (equals 3300kg strength). Engineered to match webbing strength to ensure no weak point in the harness assembly.

Available with end fitting combinations: -

- KTKT – Triple Action Karabiner Each end (**STANDARD**)
- KTST - Triple Action Karabiner and Triple Action Scaffold Hook (**STANDARD**)

Optional versions **available on request only**

- SNSN – Snap Hook Each end
- SNSD – Snap Hook and Double Action Scaffold Hook
- KDKD – Double Action Karabiner Each end
- KDSD - Double Action Karabiner and Double Action Scaffold Hook
- KDSN – Double Action Karabiner and Snap Hook
- KDST - Double Action Karabiner and Triple Action Scaffold Hook
- KSKS - Karabiner Screw Gate Each end
- KSKD - Karabiner Screw Gate and Double Action Karabiner
- KSSD - Karabiner Screw Gate and Double Action Scaffold Hook
- KSSN – Karabiner Screw Gate and Snap Hook
- KSST - Karabiner Screw Gate and Triple Action Scaffold Hook
- KTSD - Triple Action Karabiner and Double Action Scaffold Hook
- KTSN – Triple Action Karabiner and Snap Hook
- SNST - Snap Hook and Triple Action Scaffold Hook