







1T & 2T COMBINED HOISTING ASSEMBLY

Brand: OzBlok Capacity: 1.0t & 2.0t

This compact, robust, integrated hoist and trolley offers theft protection, and is perfect for locations where headroom is constrained. The ergonomic design allows for minimal operator effort to raise the load and enable exact positioning and easy traversing of heavy loads.

Australian Standard: AS 1418

Features

- Adjustable gear trolley
- Cast steel safety latches
- Factory proof tested to 1.5x W.L.L.
- Super strength zinc plated alloy load chain
- Weather protected automatic Weston brake

Industries

- Construction
- Engineering
- Infrastructure
- (Manufacturing
- Mining
- Ports
- **Utilities**

Documents

- 1t & 2t Combined Hoisting Assembly Data Sheet 2025
- 1t & 2t Combined Hoisting Assembly Manual
- HES Brochure 2025





Specifications

PRODUCT CODE	W.L.L.	STANDARD LIFT	BEAM WIDTH	MIN. HEADROOM HEIGHT	NET WEIGHT
CHCBGTOZ010	1.0t	3m	74mm - 203mm	259mm	23.5kg
CHCBGTOZ020	2.0t	3m	85mm - 203mm	376mm	43.7kg

Dimensions

PRODUCT CODE	A	В	С	D	E	F	G	Hmin
CHCBGTOZ010	240mm	382mm	312mm	203mm	26mm	30mm	44mm	259mm
CHCBGTOZ020	280mm	481mm	329mm	203mm	35mm	34mm	49mm	376mm