







# 3T & 5T COMBINED HOISTING ASSEMBLY

Brand: OzBlok Capacity: 3.0t & 5.0t

This compact, robust, integrated hoist and trolley offers theft protection, and is perfect for locations where headroom is constrained. The ergonomic design allows for minimal operator effort to raise the load and enable exact positioning and easy traversing of heavy loads.

Australian Standard: AS 1418

#### **Features**

- Adjustable gear trolley
- Cast steel safety latches
- Factory proof tested to 1.5x W.L.L.
- Super strength zinc plated alloy load chain
- Weather protected automatic Weston brake

#### Industries

- Construction
- Engineering
- ( Infrastructure
- Manufacturing
- Mining
- Ports
- **Utilities**

### Documents

- 3t & 5t Combined Hoisting Assembly Data Sheet 2025
- Combined Hoisting Assembly Manual
- HES Brochure 2025





## **Specifications**

PRODUCT CODE	W.L.L.	STANDARD LIFT		BEAM WIDTH	MIN. HEADROOM HEIGHT	
CHCBGTOZ030	3.0t	3m		74mm - 180mm	593mn	า
CHCBGTOZ050	5.0t	3m		98mm - 180mm	741mm	
Dimensions						
PRODUCT CODE	Α	В	c	D	E	F
CHCBGTOZ030	363mm	230mm	14mm	304mm	30mm	3mm
CHCBGTOZ050	436mm	260mm	18mm	330mm	42mm	3mm