









# **PUSH GIRDER TROLLEY**

Brand: OzBlok Capacity: 0.5t to 10t

This light weight, adjustable all steel push girder trolley provides a safe and simple suspension point that can be moved along variable width R.S.J's and universal beams in a controlled manner, providing added flexibility and safety when moving heavy loads horizontally.

Australian Standard: AS 1418

#### **Features**

- Anti-derailment plates
- Built in bumper guards
- Orop forged screw type adjuster
- Precision ball bearing trolley wheels
- Durable baked enamel paint protection

#### **Industries**

- Automotive
- Civil
- Construction
- Engineering
- ( Entertainment
- (V) Hire
- Infrastructure
- Lifts/Elevators
- ( Manufacturing
- ( Ports
- Warehousing

### Documents

- OB Push Girder Trolley Brochure
- OB Push Girder Trolley Manual





- 2024 Push Girder Trolley Data Sheet
- HES Brochure 2025

## Specifications

PRODUCT CODE	W.L.L.	NET WEIGHT	MIN. RADIUS CURVE	ADJUSTABLE BEAM WIDTH
PTOZ005	0.5t	5.70kg	0.6m	50mm - 210mm
PTOZ010	1.0t	7.95kg	0.8m	64mm - 210mm
PTOZ010-BLK	1.0t	7.95kg	0.8m	64mm - 210mm
PTOZ020	2.0t	14.00kg	1.1m	88mm - 210mm
PTOZ030	3.0t	24.20kg	1.4m	100mm - 305mm
PTOZ050	5.0t	36.00kg	1.0m	114mm - 305mm
PTOZ100	10.0t	64.90kg	1.3m	125mm - 305mm





PRODUCT CODE		W.L.L.		NET MIN. RADIUS CURVE		ADJUSTABLE BEAM WIDTH				
PTOZSS0	PTOZSS010 1.0t		1	12.00kg 1.0m		64mm – 203mm				
PTOZSS0	PTOZSS020 2.0t		1	19.50kg		1.1m		88mm – 203mm		
Dimensi	ions									
PRODUCT CODE	W.L.L.	A	В	с	D	E	F	G	н	
PTOZ005	0.5t	204.00mm	90.00mm	186.00mm	34.00mm	22.00mm	12.00mm	210.00mm	308.00mm	
PTOZ010	1.0t	212.00mm	92.00mm	199.50mm	34.00mm	24.00mm	15.00mm	210.00mm	323.00mm	
PTOZ010-BLK	1.0t	212.00mm	92.00mm	199.50mm	34.00mm	24.00mm	15.00mm	210.00mm	323.00mm	
PTOZ020	2.0t	256.00mm	108.00mm	241.00mm	47.50mm	33.00mm	17.00mm	210.00mm	342.00mm	
PTOZ030	3.0t	308.00mm	130.00mm	300.50mm	58.50mm	37.00mm	25.00mm	305.00mm	456.00mm	
PTOZ050	5.0t	346.00mm	149.00mm	334.59mm	71.50mm	42.00mm	26.50mm	305.00mm	472.00mm	
PTOZ100	10.0t	406.00mm	172.00mm	407.14mm	86.00mm	50.00mm	32.00mm	305.00mm	489.00mm	
PTOZSS010	1.0t	331.00mm	246.00mm	229.00mm	-	-	-	-	127.00mm	
PTOZSS020	2.0t	350.00mm	276.00mm	268.00mm	-	-	-	-	150.00mm	