AUSTRALIAN LIFTING CENTRE PTY LTD
www.austlift.com.au
ABN: 58 078 514 584

NSW Head Office
43 Frank Street, Wetherill Park, NSW 2164 Tel: 02 9757 2277 Fax: 02 9757 2922

AUSTLIFT®
LIFTING YOUR BUSINESS TO A HIGHER LEVEL

TRAILER SAFETY CHAIN HOOK SET

SPECIFICATION FOR 6MM, 8MM

AS/NZS 3776 | AS/NZS 4177.4 | ADR 62/02 | Certified




Austlift G100 Trailer Chains and Safety Hook Set are available in two sizes, each with different Towing Capacities, breaking forces, and chain size compatibility, ensuring that they meet the towing requirements for various Aggregate Trailer Masses (ATM). Fatigue tested over 20,000 times.

Kit Code	Kit Size	ATM (Max Towing Capacity)	Suitable Trailer Chain	Minimum Breaking Strength
103606	6mm	2.8ton	8mm	4.48 T
103608	8mm	5.0ton	10/13mm	8.0 T

*Note: After 13mm Grade 30 trailer chains, a non-galvanised Grade 80 or Grade 100 chain must be used.






CHAIN CONNECTOR 4 to 1 Safety Factor as per AS3776

Size	Min. Break Strength	Dimensions (mm)			
		B	C	K	D
6mm	4.48 T	16.9	8.5	44.5	7
8mm	8.0 T	22.7	10.5	63	10





EYE SLING HOOK 4 to 1 Safety Factor as per AS3776

Size	Min. Break Strength	Dimensions (mm)					
		B	D	E	H	L	L1
6mm	4.48 T	20.5	10	18.5	21	111	80
8mm	8.0 T	25	11	25	27	137	99

AUSTLIFT *Lifting your business to a higher level.*

NSW Head Office
43 Frank Street
Wetherill Park, NSW 2164
02 9757 2277

WA Office
42 Mulgal Road
Malaga, WA 6090
08 9248 6674

QLD Office
7 Durbell Street
Acacia Ridge, QLD 4110
07 3272 0777

VIC Office
475 Dohertys Road
Truganina, VIC 3029
03 9314 5525